


MEDIUM PRESSURE NIPPLES AND TUBING

Coned and Threaded Nipples

BuTech stocks pre-cut coned and threaded nipples in lengths up to 12" (305 mm). In addition, nipples can be purchased to any custom length.



Connection	Length							MAWP
	2.75" (69.9)	3.00" (76.2)	4.00" (101.6)	6.00" (152.4)	8.00" (203.2)	10.00" (254.0)	12.00" (304.8)	
1/4" M/P	20N442-*	20N443-*	20N444-*	20N446-*	20N448-*	20N4410-*	20N4412-*	20,000 PSI 1380 bar
3/8" M/P		20N663-*	20N664-*	20N666-*	20N668-*	20N6610-*	20N6612-*	20,000 PSI 1380 bar
9/16" M/P			20N994-*	20N996-*	20N998-*	20N9910-*	20N9912-*	20,000 PSI 1380 bar
3/4" M/P				20N126-*	20N128-*	20N1210-*	20N1212-*	20,000 PSI 1380 bar
1" M/P				20N166-*	20N168-*	20N1610-*	20N1612-*	20,000 PSI 1380 bar

*Complete catalog number by adding suffix **316** for 316 stainless steel or suffix **304** for 304 stainless steel

Tubing

Catalog Number	Connection	O.D.	I.D.	MAWP
20-109-*	1/4" M/P	0.250" (6.4)	0.109" (2.8)	20,000 PSI 1380 bar
20-203-*	3/8" M/P	0.375" (9.5)	0.203" (5.2)	20,000 PSI 1380 bar
20-312-*	9/16" M/P	0.562" (14.3)	0.312" (7.9)	20,000 PSI 1380 bar
20-438-*	3/4" M/P	0.750" (19.1)	0.438" (11.1)	20,000 PSI 1380 bar
20-562-*	1" M/P	1.000" (25.4)	0.562" (14.3)	20,000 PSI 1380 bar

*Complete catalog number by adding suffix **316** for 316 stainless steel or suffix **304** for 304 stainless steel. Other materials are also available, please consult factory.

BuTech offers a complete selection of austenitic seamless cold-drawn stainless steel tubing for high pressure applications where both high strength and corrosion resistance are desired. Tubing is available in standard 20-24 foot lengths (6-7 meters), however, longer lengths are available on request.



See Section T for Coning Tools, Threading Tools and Tube Vises!